

PINTEK

High Voltage Amplifier

★ **High Power Model!**

HA-305

- 300Vp-p($\pm 150V$ DC)
- 600mA_{p-p}($\pm 300mA$ DC)
- Bandwidth: $\leq 100KHz$ (150Vp-p)
- Slew Rate: 50V/us
- Gain(AMPL): 0~60(10 Turn VR)
- DC Offset: $\leq 0 \sim \pm 150V$ (10 Turn VR+SW)
- Output Resistor: 10 Ω
- Microprocess Control Protection



HA-405

- 400Vp-p($\pm 200V$ DC)
- 400mA_{p-p}($\pm 200mA$ DC)
- Bandwidth: $\leq 1MHz$ (200Vp-p)
- Slew Rate: 500V/us
- Gain(AMPL): 0~90(10 Turn VR)
- DC Offset: $\leq 0 \sim \pm 200V$ (10 Turn VR+SW)
- Output Resistor: 50 Ω
- Microprocess Control Protection

HA-805

- 800Vp-p($\pm 400V$ DC)
- 200mA_{p-p}($\pm 100mA$ DC)
- Bandwidth: $\leq 300KHz$ (400Vp-p)
- Slew Rate: 300V/us
- Gain(AMPL): 0~180(10 Turn VR)
- DC Offset: $\leq 0 \sim \pm 400V$ (10 Turn VR+SW)
- Output Resistor: 100 Ω
- Microprocess Control Protection



BP-253N



BP-250

CE

Pintek Electronics Co., Ltd

www.pintek.com.tw