

# PW-4032 100 VA DC Power Supply



## SPECIFICATIONS

Power Transformer:	E.I. Type Transformer
Max. Continual Output Power:	105VA
Max. Raised Temperature:	< 40 °C
Independent Output:	0~30V/0~3A, 5V Fixed / 0~3A; Dual Output

### Constant Voltage Characteristic

Load Regulation:	$\pm 0.01\% + 10\text{mV}$
Line Regulation:	$\pm 0.01\% + 5\text{mV}$
Ripple & Noise:	< 0.4mVrms

### Constant Current Characteristic

Load Regulation:	< 15mA
Line Regulation:	$\pm 0.01\% + 2\text{mA}$
Ripple & Noise:	< 2.5mArms

### 5V Fixed Output

Regulation:	Line Regulation < 5mV, Load Regulation < 10mV
Ripple & Noise:	< 1.5mVrms
Voltage Accuracy:	5V $\pm$ 0.25V
Max. Output Current:	3A

### Display

Voltage:	4 Digits 0.36" Green LED
Current:	4 Digits 0.36" Red LED
Accuracy:	0.05% + 3 digits

### General

Power Source:	ACV 115/230 $\pm$ 10%, 50/60Hz
Dimensions( W x H x D):	230 x 170 x 310 mm
Weight:	6.8 kg

# **PINTEK**

## **Pintek Electronic Co., Ltd**

2F No.32 Tai-Pen Rd., Shulin City, Taipei Hsien, Taiwan  
 Tel: 886-2-86859562~3 Fax: 886-2-86852081  
<http://www.pintek.com.tw>  
 E-Mail : [pintek@pintek.com.tw](mailto:pintek@pintek.com.tw) ; [pintek@ms26.hinet.net](mailto:pintek@ms26.hinet.net)

SALES AGENT