

DP-16K Differential Probe

SPECIFICATIONS:

FUNCTION / MODEL	DP-16K
Differential Voltage DC + AC peak	X1000 \pm 8 KV X100 \pm 800V
Bandwidth (-3dB)	100 MHz
Common Mode Voltage DC + AC peak	\pm 8 KV
Common Mode Voltage AC / RMS	5650 VRMS
Range (Switchable)	2(X100, X1000)
Input Impedance (Between Input)	20 M Ω // 5 pF
Each Input R//C	10 M Ω // 10 pF
Common Mode Rejection Ratio (CMRR)	60 Hz: > 10000 : 1 100 Hz: > 1000 : 1 1 MHz: > 300 : 1
DC Gain Accuracy	\pm 2%
Output Range	\pm 8 V (1 M Ω Load)
Output Impedance	50 Ω
Over Range Indicate	X1000: \pm 8 KV X100: \pm 800 V
Power Range	5 V ~ 12 VDC
Dimensions / Weight	220 x 85 x 30 mm / 450 g



ACCESSORIES:



PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net

SALES AGENT