

DP-22K_{pro} Super High Voltage Differential Probe

SPECIFICATIONS:

FUNCTION	
Differential Voltage DC + AC peak	22KV
Bandwidth (50Ω load -3dB)	120MHz(X100, X300, X1000, x3000); 60MHz(X30)
Common Mode Voltage DC + AC peak	22KV
Common Mode Voltage AC /RMS	7.8KV
Range (Switchable)	5(X30, X100, X300, X1000, x3000)
Input Impedance (Between Input)	100MΩ // 1 PF
Each Input R // C	50MΩ // 2 PF
Common Mode Rejection Ratio(CMRR)	60 Hz: > 10000 : 1 100 Hz: > 1000 : 1 1MHz: > 300 : 1
Noise (Into 50Ω Load)	≤ 1m Vrms
Accuracy	≤ ± 2%
Maximum Output Voltage	≤ ± 5V
Output Impedance	50Ω
Input Over Range Indicate	Any Range, Input Voltage Exceed the Max. Voltage 90%
Power Auto Regulation System	DC 6~12V
Power Source	External DC 9V/300mA
Accessories	BP-250, BP-276N, BP-286, BP-366, PX-502, ADP-110(or ADP-220)

ACCESSORIES:

<p>BP-266 (HV IC Clip, 7KV RMS, 3A 208L x 44W x 38H mm)</p> 	<p>BP-250 (BNC Plug to BNC Plug, 50Ω cable 100cm)</p> 	<p>BP-276N (Alligator Clip, UL 1KV CAT II, 10A)</p> 	<p>Adapter ADP-110 or ADP-220 DC 9V/300mA</p> 
<p>BP-366 (HV Banana Plug to Banana Plug, UL3239, 16AWG., 20KV DC, 10A, 150°C, 60cm, silicone wire)</p> 	<p>PX-502 (Carry Box, ABS, 380L X 167W X 140H mm, 790g)</p> 	<p>BP-286 (Test Leader, UL94V-2, 1KV RMS, 10A, ∅11.5 X 120mm)</p> 	

PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin City, Taipei Hsien, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net



SALES AGENT