


FG-109 10MHz FUNCTION GENERATOR



SPECIFICATIONS:

Main	Output Wave Form	Sine, Square, Triangle, Pulse, Anti-Pulse
	Amplitude Range	10Vpp(50Ω Load)
	Impedance	50Ω ±10%
	Attenuator	-40dB
	DC Offset	-5 ~ +5V(50Ω Load)
	Duty Range	20% ~ 80%, ~ 3MHz(Square Wave)
	Duty Resolution	1%
	Display	128x64 pixel LCD
Frequency	Sine Wave Range	0.3Hz ~ 10MHz
	Square Wave Range	0.1Hz ~ 3MHz
	Triangle Wave Range	0.3Hz ~ 3MHz
	Pulse Wave Range	0.1Hz ~ 1MHz
	Anti-Pulse Wave Range	0.1Hz ~ 1MHz
	Resolution	0.1Hz
	Accuracy	0.5%
Sweep	Sweep Rate	Max Rate 2:1
	Sweep Time	500uS ~ 4S
	Sweep Mode	Linear, Logarithmic
Amplitude Modulation	Depth	0 ~ 100%
	Frequency	1KHz(internal), DC ~ 1MHz(external)
	Carrier BW	100Hz ~ 3MHz
Frequency Modulation	Frequency	1KHz
Counter	Range	5Hz ~ 60MHz
Memory Space	20 sets of memories	
Power Source	AC115/230V ±10%, 50/60Hz	

PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net

CE

SALES AGENT