

MR-30 Digital Programmable DC MilliOHM With USB

SPECIFICATIONS:

Resistance	Accuracy	$\leq 30m\Omega$	$\pm 0.1\% + 6$	
		$> 30m\Omega$	$\pm 0.05\% + 6$	
Range	30mΩ, 300mΩ, 3Ω, 30Ω, 300Ω, 3KΩ, 30KΩ, 300KΩ, 3MΩ			
Measurement	Four-terminal method			
Sort Range	$\pm 9999\%$, +99 ~ -9999%			
Buzzer	Mute, Pass, Fail			
Over Range	“OL” indication			
Range	Resolution	Measure Current	Measure Current	Open-Terminal Voltage
~30mΩ	1 $\mu\Omega$	1A	$\pm 0.1\% + 6$	~ 1.2V
~300mΩ	10 $\mu\Omega$	100mA	$\pm 0.05\% + 6$	~ 1.2V
~3Ω	100 $\mu\Omega$	100mA	$\pm 0.05\% + 6$	~ 1.2V
~30Ω	1mΩ	10mA	$\pm 0.05\% + 6$	~ 4.5V
~300Ω	10mΩ	100mA	$\pm 0.05\% + 6$	~ 4.5V
~3KΩ	100mΩ	1mA	$\pm 0.05\% + 6$	~ 4.5V
~30KΩ	1Ω	100 μ A	$\pm 0.05\% + 6$	~ 4.5V
~300KΩ	10Ω	10 μ A	$\pm 0.05\% + 6$	~ 4.5V
~3MΩ	100Ω	1 μ A	$\pm 0.05\% + 6$	~ 4.5V
Delay Time	0.1 ~ 9999 S			
Temperature Sensor	Accuracy	0.3% + 3°C		
Memory	20 sets of memories			
Operation Environment	Temperature	0°C to 40°C		
	Humidity	20% to 80%		
Storage Environment	Temperature	-20°C to 70°C		
	Humidity	0% to 90%		
Power	AC 115V/230V $\pm 10\%$ 50/60Hz			

ACCESSORIES:



PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net

SALES AGENT